

u[sonic]WS6 WEATHER SENSOR



For six weather parameters

The u[sonic]WS is the newest, most compact and system-capable addition to the LAMBRECHT meteo weather sensor series. The sensor has no moving measuring elements and is therefore low-maintenance. The intelligent heating system works in relation to the wind speed and direction and keeps the sensor ice-free even under extreme weather conditions. The u[sonic]WS6 easily meets the special challenges of alpine and maritime applications.

- No moving measuring elements, no wear
- Six weather parameters: wind direction and speed, air temperature, rel. humidity, barometric pressure, dew point
- Intelligent heating depending on wind speed and wind direction
- Lamella shelter for accurate measurements of the temperature-humidity sensor
- Easy to install, easy to maintain

APPLICATIONS

- Professional meteorological application
- Wind turbines on- and off-shore
- Ship weather station
- Building automation and environmental engineering
- Traffic and industrial meteorology
- Wind warning and event engineering
- Photovoltaic large-scale plants
- Alpine applications

Professional Line	u[sonic]WS6
Id-No.	00.16480.000000
Meas. range wind direction	0...359.9°
Meas. range wind speed	0...65 m/s
Meas. range air temperature	-40...+70 °C
Meas. range rel. humidity	0...100 %
Meas. range barometric pressure	300...1100 mbar
Accuracy wind direction	< 2° (> 1 m/s) RMSE
Accuracy wind speed	± 0.2 m/s RMSE (v < 10 m/s); ± 2 % RMSE (10 m/s < v < 65 m/s)

Continued on page 2

Professional Line	u[sonic]WS6
Accuracy air temperature	± 0.1K (0...60 °C); ± 0.2K (-40...0 °C)
Accuracy rel. humidity	Typically ± 1.5 % (0...80 %) r. h.; ± 2 % (80...100 %) r. h.
Accuracy barometric pressure	± 0.5 mbar
Resolution wind direction	0.1°
Resolution wind speed	0.1 m/s
Resolution air temperature	0.1 °C
Resolution rel. humidity	0.1 %
Resolution barometric pressure	0.1 mbar
Trigger threshold	0.1 m/s
Output	RS 485; RS 422 (optional; please specify when ordering: Id-No.: 97.16470.000422 Configuration RS 422 output)
Protocols	NMEA 0183 Modbus RTU (optional; please specify when ordering: Id-No.: 97.16470.000001 Configuration Modbus) SDI-12 (optional; please specify when ordering: Id-No.: 97.16470.000002 Configuration SDI-12) Other protocols on request
Interface	RS485 / 422; SDI-12 (optional)
Measuring rate	0.1...10 Hz
Operating conditions	-40...+70 °C (with heating: -50...+70 °C); 0...100 % r. h.
Supply voltage	Without heating: 6...60 VDC; with heating: 24 V AC/DC ± 20 %
Current consumption	Sensor: typically 50 mA at 24 VDC; with heating: max. 10 A at 24 V AC/DC
Heating data	Factory configurable: 60 W / 120 W / 240 W (standard)
Dimensions	Ø 199 mm; height 238 mm
Housing	Seawater resistant aluminium
Protection class	IP 66; IP 67
Weight	Approx. 3.1 kg
Standards	Low voltage guide line: 72/23 EWG Protection class: DIN EN 60529 DIN EN 50121-4:2016 Salt fog: EN 60945 Cold test Ad acc. to DIN EN 60068-2-1 (01/2008) Condensation test CH acc. to ISO 6270-2 (09/2005) and DIN EN ISO 12944-6 (07/1998), category C4 Salt mist test based on DIN EN ISO 7253 (04/2002) and DIN EN ISO 12944-6 (07/1998), category C4
EMC standards / Electrical safety	DIN EN 60945; DIN EN 61000-4-2, 3, 4, 6, 11
Options (order separately)	00.16480.000200 u[sonic]WS6 with bayonet plug 32.16420.066100 Cable 10 m; 12-pole bayonet plug, ready-for-use
Accessories (order separately)	32.16470.060000 sensor cable, 15 m, 8-pol. M16-plug

As of: 17.03.2025